

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 January 2001 (18.01.2001)


PCT

(10) International Publication Number  
**WO 01/03756 A1**

- (51) International Patent Classification<sup>7</sup>: **A61M 1/36**, B01L 3/14 (72) **Inventors: JORGENSEN, Glen, E.**; 38 Beverly Drive, Marlboro, MA 01752 (US). **BERCKMANS, Bruce, III**; 2426 Country Oaks Lane, Palm Beach Gardens, FL 33410 (US).
- (21) International Application Number: PCT/US00/18553
- (22) International Filing Date: 7 July 2000 (07.07.2000) (74) **Agents: RUDISILL, Stephen et al.**; Jenkins & Gilchrist, Suite 3200, 1445 Ross Avenue, Dallas, TX 75202-2799 (US).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/142,886 8 July 1999 (08.07.1999) US (81) **Designated States (national)**: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (71) **Applicant: IMPLANT INNOVATIONS, INC.** [US/US]; 4555 Riverside Drive, Palm Beach Gardens, FL 33410 (US). (84) **Designated States (regional)**: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian

[Continued on next page]

(54) Title: PLATELET CONCENTRATION SYRINGE KIT



(57) **Abstract:** A single-use system for separating blood and producing platelet concentrates includes an elongated container for receiving blood from a patient. The container has a movable plunger mounted within the blood container for expressing blood fractions separated during centrifugation of the container through a first port mounted at one end of said container, a second port mounted on the plunger, and a third port mounted on a plunger rod attached to the plunger.



WO 01/03756 A1



patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *With international search report.*

**PLATELET CONCENTRATION SYRINGE KIT****Field of the Invention**

This invention relates to processing whole blood into fractions and, more particularly, to improvements in blood processing systems for separating platelet-rich plasma from autologous blood.

**Background of the Invention**

The science and effectiveness of using platelet-rich plasma derived from the patient's own blood in surgery are documented in medical, trade, and science journals. A known method for the preparation of platelets from whole blood is described in the American Association of Blood Bank's Technical Manual, 12th Edition, 1996, at pages 700-701, Method 9.11. A system employing this method collects the patient's whole blood into a collection unit with two integrally attached transfer containers. The blood is collected into the collecting container, the other two transfer containers are collapsed, and the two transfer containers with the collecting container are subjected to a Asoft spin@ in a centrifuge, which brings the plasma to the top of the collecting unit, leaving red cells at the bottom. In the next step, the collecting container containing the blood fractions are squeezed in a plasma extractor to force the platelet-rich plasma into one of the transfer containers through a connecting tube. A fraction comprising red cells remains behind in the collecting container, which is then removed. Next, the two transfer containers, the first being empty and the second containing the plasma, are subjected to a Aheavy spin@ in a centrifuge to concentrate platelets at the Abottom@ of the second transfer container, leaving a platelet-poor fraction of the plasma (PPP) above the platelet concentrate (PC) in the second transfer container. The following step squeezes the second transfer container to express the PPP into the first transfer container. The platelet concentrate (PC) is then re-suspended and collected for use. This system uses a process requiring six separate steps, including two centrifugal steps and two separation steps. The terms Alight spin@ and Aheavy spin@ are defined in Table 10.5-1 at page 716 of the AABB Technical Manual.

An alternative method of separating blood fractions is discussed in U.S. Patent No. 5,102,407 and referred to as the AAmsterdam@ method. Instead of two spins, soft then hard, as discussed above, a single hard spin is used in which three fractions are separated, that is, a relatively platelet-free plasma, red blood cells, and an intermediate Abuffy coat@ layer which contains platelets and leukocytes.

-2-

The usual procedures often employ pliable plastic bags which make it difficult to separate the blood fractions accurately. Consequently, improvements have been needed. The present invention is embodied in a new blood separation kit which provides a more convenient and efficient means for separating a patient's blood and in particular for recovering platelets.

#### Summary of the Invention

The invention provides a single use system for separating blood and preferably for producing platelet concentrates (PC). In one embodiment, the system is in the form of a syringe kit including disposable components supplied in sterile disposable packaging, and having all of the components required to draw blood from the patient, prevent blood coagulation, separate the sample into fractions including platelet concentrate, and deliver the platelet concentrate to a surgical site. More precise separation of the separated blood fractions is possible, compared to the results achieved with pliable plastic bags. Such a system will be useful to medical and dental practitioners.

The invention may be generally described as including an elongated container, preferably cylindrical, which is adapted to be placed in a centrifuge for separating the fractions of blood introduced into the container. The container is equipped with a first port through which the blood fractions can be expelled by a plunger movably fitted within the container. The first port is located at a first end of the container and a second port is located on the movable plunger. Both ports are normally closed and they are opened from outside the container as required for removal of blood fractions. The plunger is equipped with a detachable hollow plunger rod adapted to open the second port when the plunger rod is attached to the plunger. A third port is mounted at the end of the plunger rod, the third port also is normally closed unless opened from outside the plunger rod.

In one embodiment of the invention, the container is in the form of a syringe barrel fitted with a moveable plunger. The syringe barrel is charged with a patient's blood and all of the centrifugal and separation steps are performed while the blood is in that container. The syringe barrel is adapted for use in a centrifuge, and has valves fitted at one end and within the plunger, making it possible to collect blood, centrifuge the blood in the syringe barrel, expel red blood cells after the first or soft spin, centrifuge the remaining platelet-rich plasma and expel platelet-poor plasma after the second or hard spin. The platelet concentrate

-3-

remains in the syringe barrel, where it can be re-suspended in a medium or media that can be introduced into the container through one of the valves.

In another embodiment, the container of the invention is given a Ahard@ spin, omitting the Asoft@ spin. Three fractions are formed, the first fraction, the red blood cells, is expelled through the first port, then the second fraction, platelet-poor plasma, is expelled through the second and third ports, leaving the third layer, consisting of platelets and plasma, for further processing.

The separation of blood fractions may be carried out manually after centrifuging the whole blood in the container. Alternatively, the separation of blood fractions could be carried out automatically in centrifuge equipment having facilities for opening the ports after it has been determined that the desired separation has been made.

Associated with the container preferably will be a needle assembly for drawing a patient's blood and which is adapted to transfer the blood into the syringe container directly or into a separate container for subsequent transfer into the syringe container. One or more waste bags adapted to receive platelet-poor plasma and red blood cells from the syringe cylinder after the soft and hard spins may be part of the syringe kit.

#### Brief Description of the Drawings

FIG. 1 is an isometric view of a elongated syringe container and associated components.

FIG. 2 is a longitudinal section through FIG. 1.

FIG. 3 shows a blood-collector needle.

FIG. 4 shows a waste bag.

FIGS. 5a through 5e show use of the syringe embodiment to prepare platelet concentrate.

#### Description of the Illustrative Embodiments

The figures illustrate a syringe embodiment of the invention adapted for manual handling in separation of blood fractions. Blood drawn from a patient is introduced into a syringe, the syringe is placed in a centrifuge and spun at the appropriate speed for a suitable period of time to cause the blood to be separated into at least two fractions. Alternatively, the separation may be automated and the blood fractions separated without manual handling of the syringe container.

-4-

FIG. 1 shows an elongated container 10, bearing graduated marks 12 to indicate the volume of its contents (not shown). The container has a first port, shown in the drawing as including a spring-loaded ball seat valve 14, at a first end 16 and a radially-extending flange 18 at its other end. A plunger 20 fits slidably within the container and prevents blood from passing between the wall of the container and the plunger. The plunger has a through passage 22 fitted as a second port, also shown as a spring-loaded ball seat valve 24 (FIG. 2). The valve 24 could be omitted if desired, in which case, it would be necessary to temporarily seal the opening while the container is being centrifuged to separate the blood fractions. A tubular plunger rod 26 is adapted at one end 28 to engage the spring-loaded ball seat valve 24. The plunger rod has another spring-loaded ball seat valve 30 at its other end remote from the plunger. The valves 14, 24 and 30 may have a ALuer@ fitting, which has a coupling 15, 25 and 31, respectively, for removably connecting to another article (for example, a hose). This type of valve is normally closed when nothing is connected to its coupling, and the valve can be opened when the protruding feature of a mating connector forces the ball away from the valve seat. It should be understood that the valves need not be the spring-loaded ball seat valves shown in the drawings, but may be other types capable of preventing the escape of the blood components and of being opened when needed, for example a valve in which a silicone plunger seals against a conical valve seat, the compression of which closes the valve until activated. More broadly, the ports may include other means for blocking flow of the blood components rather than the valves in the figures.

The container 10 and associated parts of the kit, particularly the plunger 20 and plunger rod 26, differ from conventional pliable plastic bags in being made of relatively stiff materials, for example polycarbonate, polypropylene, ABS or equivalents. It is an advantage of the present invention that, since the container walls are relatively rigid, the problems associated with separating blood fractions in a pliable bag are avoided. Moving the plunger within the container creates minimal disturbance of the separated blood layers, thereby enabling a more precise separation to be made.

FIG. 3 shows a needle 32 for taking blood from a patient connected to one end of a tube 34 which has at its other end a fitting 36 that is adapted to connect to any of the couplings 15, 25 or 31. Thus, blood may be introduced directly into container 10 through

-5-

valve 14 or alternatively, blood may be directed to a separate bag for subsequent transfer into the container for separation.

FIG. 4 shows a waste bag 40, typically but not necessarily a pliable plastic bag, connected to one end of a tube 42 which has at its other end a fitting 44 that is adapted to connect to any of the couplings 15, 25 or 31, thereby opening the associated valve. The tube 42 is fitted with a tubing clamp 46. The container 10 and associated parts shown in FIGS. 1-4, inclusive, comprise the syringe kit of this embodiment of the invention. The container 10, shorn of associated parts (plunger rod 26, needle 32 and tube 34, and waste bag 40 and tube 42) may be adapted for fitting in a centrifuge bucket (not shown) and used to separate blood into its fractions and to prepare platelet concentrate, as is described with reference to FIGS. 5a-5e, inclusive.

In FIG. 5a, the plunger 20 is at the top of the container 10, near the flange 18, the needle 32 is connected to check valve 14, which is held open, the waste bag 40 is connected to the plunger check valve 24 holding that valve open, and the clamp 46 is open. The container may be empty or it may contain a small amount of a blood anti-coagulant. When the needle 32 draws blood from a patient, the blood flows into the container under pressure from the patient, displacing air from the container 10, which air is received in the waste bag 40. When the container 10 is charged with blood, the waste bag 40 and needle 32 are decoupled from the valves 14 and 24, which are closed by the associated springs. Alternatively, the waste bag 40 is not used and instead, the plunger 20 may be used to extract blood directly from the patient in a manner similar to a conventional syringe. The container is subjected to a light spin in a centrifuge (not shown). As is shown in FIG. 5b, this step separates red blood cells (pRBC) from platelet-rich plasma (PRP). In the next step, shown in FIG. 5c, the waste bag is connected to valve 14, and the plunger rod 26 is connected to the plunger via the valve 24. The valves 14 and 24 and the waste bag clamp 46 are all open, but the valve 30 at the free end of the plunger rod is closed. The plunger rod 26 is used to push the plunger into the container, expelling the red blood cells into the waste bag 40. The container now contains primarily platelet-rich plasma. The clamp 46 is closed, and the plunger rod and the waste bag 40 are decoupled from the container, thus closing valves 14 and 24.

-6-

The container 10, shorn of the bag and plunger rod, as shown in FIG. 5d, is next subjected to a hard spin, which concentrates platelets at the bottom end 16 of the container 10, leaving platelet-poor plasma (PPP) above the platelet concentrate. The final step in the process, that of removing the platelet-poor plasma from the container, is illustrated in FIG.

5 5e. The plunger rod 26 is again attached to the plunger 20, and the waste bag 40 is coupled to the free end of the plunger rod through the valve 30. The valves 24 and 30 and the clamp 46 are all open, and the valve 14 is closed. The plunger is driven toward the lower end 16 of the container, and the platelet-poor plasma is forced through the passageway in plunger rod 26 and the tube 44 into the waste bag. The clamp 46 is then closed, and the waste bag 40  
10 and, if desired, the plunger rod 26 may be removed from the container. With the waste bag removed, the plunger rod valve 30 will close, so failure to remove the plunger rod will not affect the contents of the container. The container 10 is now left with the platelet concentrate in it.

The above description covers a simple manual operation in which the syringe kit is  
15 used in a particular manner to separate blood into three fractions by successive soft and hard spins. It is also feasible to use only one Ahard@ spin to separate the blood in a single step into three fractions (i.e., red blood cells, plasma and an intermediate layer containing platelets). The three fractions can be separated by expelling both the plasma and red blood cells separately or simultaneously, leaving the intermediate layer for further processing.

20 Alternatively, such manual operations can be automated.

It should be understood that the syringe kit described above is a preferred embodiment, but that modifications may be made without departing from the scope of the invention as defined by the following claims.



-7-

## WHAT IS CLAIMED IS:

## 1. A blood separation kit comprising:

(a) an elongated hollow container having a first end and a second end and comprising a first port mounted at said first end for admitting liquid to or expelling liquid  
5 from said container, said port being closed unless opened by a fitting attached to said port;

(b) a plunger movably disposed within and engaging the walls of said container of (a), said plunger comprising

(1) a passageway through said plunger communicating with the interior of said container of (a), and

10 (2) a second port for expelling liquid mounted within said passageway of (b)(1), said port being closed unless opened by a fitting attached to said port; and

(c) a plunger rod having a passageway therein and adapted to engage said plunger of (b), said plunger rod comprising

15 (1) means for engaging said plunger to provide communication with the inside of the container of (a) via the passageway in the plunger of (b) to the passageway in said plunger rod,

(2) a third port for expelling liquid mounted at the end of said plunger rod opposite said means for engaging said plunger, said third port being closed  
20 unless opened by a fitting attached to said third port.

## 2. A blood separation kit of Claim 1, further comprising:

(d) a needle set comprising:

(1) a hollow needle for taking a sample of a patient's blood;

(2) a hollow tube attached to and communicating with said needle  
25 for transferring said patient's blood to the container of (a); and

(3) a fitting adapted to engage the first port of (a) and to open said first port.

## 3. A blood separation kit of Claim 1, further comprising:

(e) a waste bag having a hollow tube connected to and communicating  
30 with the interior of said bag for receiving separated blood fractions;

-8-

(f) a fitting adapted to engage the first and third ports (a) and (c)(2) respectively and to open said first and third ports; and

(g) a clamp mounted on the tube of (e) for opening and closing the hollow tube of (e).

5 4. A method of collecting and separating a patient's blood and recovering a platelet-rich concentrate comprising:

(a) collecting the patient's blood using a needle set comprising a hollow needle having attached tubing and a fitting adapted to engage a first port in an elongated container fitted with a movable plunger having a second port therein;

10 (b) transferring said blood through said first port into said elongated container;

(c) centrifuging said blood in said container and separating said blood into platelet-rich plasma and red blood cells;

(d) displacing the red blood cells separated in (c) from said container by  
15 moving said plunger towards said first port and expelling said red blood cells into a waste bag through tubing attached to said first port;

(e) removing said waste bag of (d) centrifuging said platelet-rich plasma remaining in said container and separating a platelet-rich concentrate from a platelet-poor plasma;

20 (f) attaching a hollow plunger rod having a third port therein to said plunger and displacing the platelet-poor plasma separated in (e) from said container by moving said plunger towards said first port and expelling said platelet-poor plasma through said second port of said plunger and said third port of said plunger rod into a waste bag attached to the plunger rod; and

25 (g) recovering the platelet-rich concentrate separated in (e) and remaining in said container.

5. A method of collecting and separating a patient's blood and recovering a platelet-rich concentrate comprising:

(a) collecting the patient's blood using a needle set comprising a hollow  
30 needle having attached tubing and a fitting adapted to engage a first port in an elongated container fitted with a movable plunger having a second port therein;

-9-

(b) transferring said blood through said first port into said elongated container;

(c) centrifuging said blood in said container and separating said blood into platelet-poor plasma, red blood cells, and platelet-rich concentrate;

5 (d) displacing the red blood cells separated in (c) from said container by moving said plunger towards said first port and expelling said red blood cells into a waste bag through tubing attached to said first port;

(e) removing said waste bag of (d) and attaching a hollow plunger rod having a third port therein to said plunger and displacing the platelet-poor plasma separated  
10 in (c) from said container by moving said plunger toward said first port and expelling said platelet-poor plasma through said second port of said plunger and said third port of said plunger rod into a waste bag attached to the plunger rod; and

(f) recovering the platelet-rich concentrate separated in (c) and remaining in said container.

15 6. A blood separation kit of claim 1, wherein said first, second, and third ports comprise valves positioned to prevent expelling blood fractions during centrifugation of blood in said container.

7. A blood separation kit of claim 1, wherein said ports comprise Luer fittings.




FIG. 1

2/3




FIG. 4

FIG. 2

FIG. 3




FIG. 5b

FIG. 5a




FIG. 5d

FIG. 5e

FIG. 5c

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/18553

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 A61M1/36 B01L3/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 44 45 030 A (HERAEUS INSTR GMBH) 27 June 1996 (1996-06-27) column 4, line 16 -column 5, line 49 figures 1,2	1,2,7
A	WO 91 17778 A (UNES AS) 28 November 1991 (1991-11-28) abstract figure 1	1,2
A	US 5 858 253 A (HOLM NIELS ERIK) 12 January 1999 (1999-01-12) column 8, line 27 -column 11, line 12 figures 1,19	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

18 September 2000

Date of mailing of the international search report

22/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Schönleben, J

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/18553

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 4445030	A	27-06-1996	NONE	
WO 9117778	A	28-11-1991	AT 134883 T	15-03-1996
			AU 645574 B	20-01-1994
			AU 7902291 A	10-12-1991
			CA 2082960 A	15-11-1991
			CN 1056632 A,B	04-12-1991
			CS 9101416 A	19-02-1992
			DE 69117750 D	11-04-1996
			DE 69117750 T	05-09-1996
			DK 528949 T	22-07-1996
			EP 0528949 A	03-03-1993
			ES 2084164 T	01-05-1996
			FI 925171 A	13-11-1992
			GR 3019250 T	30-06-1996
			HU 67381 A,B	28-04-1995
			IE 73213 B	07-05-1997
			IL 98076 A	30-05-1994
			JP 2963539 B	18-10-1999
			KR 156008 B	15-10-1998
			MX 170505 B	26-08-1993
			NO 177953 B	18-09-1995
			NZ 238111 A	27-04-1994
			PT 97666 A,B	30-06-1993
			SK 279151 B	08-07-1998
			US 5480378 A	02-01-1996
			ZA 9103638 A	26-02-1992
US 5858253	A	12-01-1999	US 5603845 A	18-02-1997
			US 6027655 A	22-02-2000
			US 5776336 A	07-07-1998
			US 5741428 A	21-04-1998
			US 5792344 A	11-08-1998
			AU 708820 B	12-08-1999
			AU 6706698 A	02-07-1998
			AU 688390 B	12-03-1998
			AU 7889794 A	25-05-1995
			BR 9404484 A	11-07-1995
			CA 2136148 A	20-05-1995
			CN 1108964 A,B	27-09-1995
			CZ 9402806 A	13-12-1995
			EP 0654669 A	24-05-1995
			FI 945401 A	20-05-1995
			HU 70365 A,B	30-10-1995
			IL 111524 A	15-06-1998
			IL 121003 A	16-08-1998
			IL 121004 A	16-08-1998
			JP 7185393 A	25-07-1995
			NO 944422 A	22-05-1995
			NZ 264859 A	28-10-1996
			NZ 299081 A	28-10-1996
			PL 305907 A	29-05-1995
			RU 2133468 C	20-07-1999
			SG 49212 A	18-05-1998
			SK 138394 A	07-06-1995
			ZA 9408564 A	02-05-1995